

Nom Size.	Available Lengths (A)	Top Upset		Top Upset		Bore (E)	Drive Section		Wt. of 40ft. Length
		API Box Left-hand Conn.	OD (C)	Right-hand Conn.	OD (D)		Across Corners (F)	Across Flats (G)	
(in.)	(in.)		(in.)		(in.)	(in.)	(in.)	(in.)	(lb.)
3 1/2	40, 46	6 5/8 REG.	7 3/4	NC31 (2 7/8 IF)	4 1/8	2*	3.937	3 1/2	1,300
		4 1/2 REG.	5 3/4						1,200
4 1/2	40, 46	6 5/8 REG.	7 3/4	NC38 (3 1/2 IF)	4 3/4	2 1/4	4.781	4 1/4	1,740
5 1/4	40, 46, 54	6 5/8 REG.	7 3/4	NC46 (4 IF)	6 - 6 3/8	3	5.900	5 1/4	2,550
				NC50 (4 1/2 IF)	6 1/8 - 6 3/8				
6	40, 46, 54	6 5/8 REG.	7 3/4	NC56 5 1/2 IF	7	3 1/2	6.812	6	3,040

Ordering instructions, please specify:

- Nominal size
- Length (A)
- Bore ID (E)
- Size and type of top connection
- Size and type of bottom connection
- Top Upset OD (C)
- Bottom Upset OD (D)
- Type of shipping scabbard, (Rathole drilling scabbards are available on request)

\*Not an API standard

## Square Kelly Specification Table

Nom Size.	Available Lengths (A)	Top Upset		Top Upset		Bore (E)	Drive Section		Wt. of 40ft. Length
		API Box Left-hand Conn.	OD (C)	Right-hand Conn.	OD (D)		Across Corners (F)	Across Flats (G)	
(in.)	(in.)		(in.)		(in.)	(in.)	(in.)	(in.)	(lb.)
3	40, 46	6 5/8 REG.	7 3/4	NC31 (2 7/8 IF)	4 1/8	2*	3.937	3 1/2	1,300
		4 1/2 REG.	5 3/4						1,200
3 1/2	40, 46	6 5/8 REG. 4 1/2 REG.	7 3/4 5 3/4	NC38 (3 1/2 IF)	4 3/4	2 1/4	4.437	3 1/2	1,320
4 1/4	40, 46, 54	6 5/8 REG.	7 3/4	NC46 (4 IF)	6 - 6 3/8	3	5.900	5 1/4	2,550
				NC50 (4 1/2 IF)	6 1/8 - 6 3/8				
5 1/4	40, 46, 54	6 5/8 REG.	7 3/4	NC56 5 1/2 IF	7	3 1/2	6.812	6	3,040
6	40, 46, 54	6 5/8 REG.	7 3/4	6 5/8 REG.	7 3/4	3 1/2	7.625	6	3,700

Ordering instructions, please specify:

- Nominal size
- Length (A)
- Bore ID (E)
- Size and type of top connection
- Size and type of bottom connection
- Top Upset OD (C)
- Bottom Upset OD (D)
- Type of shipping scabbard, (Rathole drilling scabbards are available on request)

\*Not an API standard

For reference purpose only